

WATER DAMAGE COMBI MACHINES

Dryer and turbine in the same unit. With our combi machines you can easily switch between suction drying or pressure drying a layered construction. Installation is simple, fast and very reliable.

COMBI MACHINE CTR K150XT

Patented machine with dehumidifier and turbine in the same unit, which makes it very easy to change between suction and pressure drying of a layered construction.



CTR K150XT is our largest combi machine and can be used when drying layered constructions of up to 40 m², depending on material. The machine has an integrated Corromatic flow meter that shows the airflow through the machine.

SOME ADVANTAGES OF CTR K150XT:

- ▶ Quiet
- ▶ Easy to install, fast and safe
- ▶ Equipped with Corromatic Flow meter

TECHNICAL DATA

Capacity +20°C, 40% RH	35 l/day*
Dry air volume	150 m ³ /h
Pressure	260 mbar
Power supply	230 V / 50 Hz
Power consumption	1 600 W
Noise level (3 m)	44-49 dB
Weight	49 kg
Size (L x W x H)	550 x 470 x 930 mm
Article number	00841

*Depending on the installation

WELL THOUGHT DESIGN



- 1 Equipped with pull handle and large wheels for easy movement.
- 2 Equipped with an easy-grip handle that makes it easy to carry.
- 3 Equipped with Corromatic flow meter that shows the airflow through the machine.
- 4 Rubber feet protect the floor from drag marks.

DRYING TECHNIQUES



Pressure drying is one of the most effective and fastest commercially available methods for drying layered structures.



Suction drying should always be used as a first stage when drying floors on concrete slabs, where the water has leaked down into the fill or insulation under the floating floor.

CAN BE COMBINED WITH

Hygrostat HR1-5.....	p. 84
Hygrostat HMH1-10.....	p. 84
WS4 ES.....	p. 54
Flexifilter.....	p. 56

ACCESSORIES

Hose ø51 mm for bridging.....	p. 91
Hose system C16.....	p. 88
Hose system C25.....	p. 88
Hose ø51 mm.....	p. 91
Replacement filter (21406).....	p. 93
Silencer.....	p. 90
Corrofilter Inline.....	p. 55
Corrofilter Inline H13.....	p. 55